

# Lubricants

Not all oils are usable in pneumatic tools. Some oils can swell O-rings, degrade the gaskets and shorten tool life. SENCO's oil is specifically formulated to work with a variety of viton, Buna-N, polyurethane and other rubber seal compounds. If you choose the proper SENCO lubricants and follow the directions precisely, you can extend the performance and life of your tools.



## Pneumatic Tool Oil

- Premium-grade oils formulated with high-quality naphthenic distillate stocks
- Contains a carefully balanced rust and oxidation inhibitor with an effective antifoamant

*1/2 Pint (24 per case)*  
PC0101

*Quart (12 per case)*  
PC0102

*Gallon (4 per case)*  
PC0103



## Moisture Shield Lubricant

- Specifically recommended for internal lubrication for tools operating at ambient temperatures ranging upward from -20°F
- Special additives to provide extreme pressure capability, rust and corrosion protection

*Quart (12 per case)*  
PC0345

*(for use in cold weather and/or high moisture areas)*



## Compressor Pump Oil

- Recommended for all SENCO oil splash compressors
- Formulated with high-quality paraffin distillate stocks
- Contains an effective antifoamant, rust and oxidation inhibitor

*Quart (12 per case)*  
PC0344

*1/2 Pint (24 per case)*  
PC0355



## Tool Lubricant

- Multipurpose grease with long life and antirust properties
- Contains special additive to reduce the stick slip normally experienced in pneumatic applications
- Specially formulated to be compatible with SENCO O-rings and seals
- Resistant to water washout

*4-oz. (36 per case)*  
YB0123



## Tool Cleaner

- 100% biodegradable cleaner
- Effective and safest way to remove tar, glue and dirt from most tools
- Rinses easily with water

*4-oz. (24 per case)*  
PC0677



## Tool Coating

- Dry film technology keeps tar and glue from building up on tools
- Fewer misfeeds and faster cycling

*4-oz. (24 per case)*  
PC0676